

GV-ASNet



The optional GV-ASNet is the network expansion module for GV-AS100, GV-AS110 and GV-AS120. With the GV-ASNet, GV-AS100/GV-AS110 / GV-AS120 can be connected to the GV-ASManager and you can access the Web interface of GV-AS100/GV-AS110 / GV-AS120.

KEY FEATURES

- Add TCP/IP networking capability to GV-AS100/GV-AS110 / GV-AS120
- Access GV-AS100/GV-AS110 / GV-AS120's features through Web-based interfaces
- Support 2 units of GV-Readers and GV-GF Fingerprint Readers

SPECIFICATIONS

CPU	8-bit RISC microprocessor
Power	100 ~ 240V AC, 50 ~ 60Hz
Battery	12V, 5Ah and 12V, 12Ah
Reader Port	1 RS-485 interface only for GV-Readers and GV-GF Fingerprint Readers (Max. 2 readers)
Communication Protocol	RS-485
Operating Temperature	0 °C ~ 65 °C / 32 °F ~ 149 °F
Operating Humidity	10 ~ 90% RH (non-condensing)
Dimensions (W x H x D)	118.3 x 74 x 40 mm / 4.7 x 2.9 x 1.6 in
Weight	300 g / 0.66 lb
Certification	CE, FCC, RoHS